



RT2A4MB3C

RT2A4MB

SPECIFICATIONS

LED TORCH LIGHT	
Head LED	Two 35lm LED
POWER	
Charger	12VDC/1A (5.5mm) power supply
Battery	Dedicated battery, user replaceable, 7.4V lithium battery, 10.4Wh capacity, 5 hours battery power time
Charge	12VDC/1A power charge, 2 hours charging time
Power Saving	Auto power off, real time battery level indicator
STORAGE	
Interface	Micro USB (USB mass Storage)
Storage Capacity	8GB (built-in)
SYSTEM SPECIFICATION	
Screen	4.0 inch TFT 800*RGB*480(WVGA) resolution, 16.7M Color, adjustable back light brightness
Operation method	13 control keys
Language	Chinese,English,French,Spanish,Russian.. more than 10 user select
Auto power off	Disable/ 5-60 minutes
Keypad tone	Enable/Disable
System Upgrade	online upgrade through USB using windows computer
WORKING ENVIRONMENT AND SPECIFICATIONS	
Operation Temperature	-10°C ~ +55°C
Operation Humidity	30% - 90%
Product Dimension	175x113x37mm

Disclaimer: Design & specifications subject to change without prior notice.

ROVER HD COMBINE TESTER
(TVI+AHD+CVI+ANALOG)
MULTI-METER DIGITAL
HD COLOR BAR

RT2A4MB RT2A4MB3C



SPECIFICATIONS

MODEL	RT2A4MB		RT2A4MB3C
ANALOG VIDEO TEST			
Video Format	NTSC		
Signal Level	1Vpp		
Input/Output	Dual BNC connector (Video In/Video Out)		
Video Digital Zoom, Screen shot	Supports 8 level portion view, take video snap shot, record video		
Analog Video Generator	Generate NTSC video signal of various test pattern		
ANALOG HD TEST			
Video Format	HD CVI , AHD , HD TVI	HD CVI3.0, AHD 3.0 , HD TVI3.0	
Signal Level	1Vpp		
Analog Video Generator	Generate NTSC video signal of various test pattern, Generate HD-CVI,HD-TVI,AHD video signal of various test pattern(720P/1080P)		
Input/Output	Dual BNC connector (Video In/Video Out)		
Video Digital Zoom, Screen shot	Supports 8 level portion views, take video snap shot, record video		
POWER			
Output	12VDC/1A 4mm connector, 1.6mm pin diameter		
AUDIO			
Input	1 Channel		
PTZ CONTROL			
Communication Port	RS485		
Protocol	Dahua, Pelco-D/P, Samsung, Panasonic, Lilin, Yaan.. more than 30 protocols		
Baud Rate	150, 300, 600, 1200, 2400, 4800, 9600, 19200bps		
DATA MONITOR			
Baud Rate	150, 300, 600, 1200, 2400, 4800, 9600, 19200bps		
RECORD PLAYBACK			
Video Playback	frame by frame playback, digital zoom, full screen play, fast forward/rewind, delete file, fast switching of files		
Screen shot image Playback	digital zoom display, full screen display. Supports files to delete, before and after the document, fast switching		

Disclaimer: Design & specifications subject to change without prior notice.