



**ROVER 4/8 CH H.265+ 8.0MP  
NON-REAL TIME HIGH DEFINITION  
6 IN 1 DVR, 1 SATA , 220VAC, NTSC**

**RXH1904TGL  
RXH1908TGL**



## FEATURES

- Support 4/8 ch 8M non-real time encoding;
- Support XVI,AHD, TVI,CVI, CVBS, IP video input;
- Support VGA maximum 1080P output, HDMI up to 4K output;
- Mini 1U Case, 1SATA(Up to 8TB);
- 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 4G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function;
- Support WEB, CMS, VMS Platform;
- Support coaxial control;

## SPECIFICATIONS

MODEL	RXH1904TGL	RXH1908TGL
<b>VIDEO</b>		
Codec	H.265+	
Preview	4*8M@15fps (AHD) 4*5M@20fps (6in1) 4*4M@18fps (6in1)	8*8M@14fps (AHD) 8*5M@20fps (6in1) 8*4M@18fps (6in1)
Encode	4*8M@8fps(AHD); 4*5M@14fps (6in1); 4*4M@18fps (6in1); 4*3M@21fps (6 in 1) 4*1080P(6 in 1)	8*8M@8fps(AHD); 8*5M@14fps (6in1); 8*4M@18fps (6in1); 8*3M@21fps (6 in 1) 8*1080P(6 in 1)
Decode	4*8M@6fps(AHD); 4*5M@8fps (6in1); 4*4M@8fps (6in1); 4*3M@8fps (6 in 1) 4*1080P@8fps(6 in 1)	8*8M@6fps(AHD); 8*5M@8fps (6in1); 8*4M@8fps (6in1); 8*3M@8fps (6 in 1) 8*1080P@8fps(6 in 1)
Multi-mode	Analog:4*8M@8fps; Hybrid:2*5M@15fps (analog)+2*5M@15fps(network) IP: 4*5M; 4*3M; 8*1080P	Analog:8*8M@8fps; 8*5M@14fps Hybrid:4*5M@20fps (analog)+4*5M@14fps(network) IP: 8*3M; 4*5M
Playback	4ch	8ch
<b>AUDIO</b>		
Compression	G.711a	
Intercom	Support	
<b>MANAGEMENT</b>		
Record Mode	Manual>Alarm>Motiondetection>Timing	
Search Mode	Inquire by Time/Calendar/Event/Channel	
Storage Mode	HDD Storage	
Backup	Network, USB, SATA	
<b>INTERFACE</b>		
Video Input	4*BNC (Support Coaxitron)	8*BNC (Support Coaxitron)
HDMI Output	1*HDMI (MAX:4K)	
VGA Output	1*VGA (MAX:1080P)	
Audio I/O	4/1	6/1
Alarm I/O	-	4/1
Ethernet Port	1*10/100Mbps Ethernet port, RJ45 port	
PTZ Control	1*RS485, Support for multiple PTZ protocol	
USB Port	2*USB2.0 ports	
HDD	1*SATA interface(Up to 8TB)	
<b>GENERAL</b>		
Temperature	0°C - + 55°C	
Humidity	10% -90% RH	
Power Supply	12V/2A	
Consumption	<10W (Without HDD)	
Weight	Around 1kg	
Dimension	255mm(L)*236mm(W) *44mm(H)	

Disclaimer: Design & specifications are subject to change without prior notice.