



**ROVER 16CH H.265+ 8.0MP XVI
NON-REAL TIME HIGH DEFINITION
6 IN 1 DVR W/ FACE DETECTION
FUNCTION, 4 SATA , 220VAC, NTSC**

RXH1916FGL



SPECIFICATIONS

FEATURES

- Support 16ch 8M non-real time encoding;
- Supports AI Human Body Detection;
- Supports AI Face Detection;
- Support AHD, TVI,CVI, CVBS, IP video input;
- Support VGA maximum 1080P output, HDMI up to 4K output;
- 1.5U Case, 4 SATA(Up to 8TB);
- 1*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 4G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS platform;
- Support coaxial control;

INTERFACE



MODEL		RXH1916FGL
VIDEO		
Codec		H.265+/H.265/H.264
Preview		16ch 4K@ 15fps(AHD)/ 16ch 5M@ 20fps(6 in 1)
Encode		16ch 4K@ 8fps(AHD)/ 16ch 5M@ 13fps(6 in 1)
Decode		8ch 4K@ 8fps(AHD)/ 16ch 5M@13fps(6 in 1)
Multi-mode		Analog:16ch 4K/16ch 5M Digital to analog conversion:support Hybrid:4ch 4K (analog)+4ch 4K(network) IP: 32ch 1080P/16ch 3M/8ch5M
Playback		16/8ch
SMART		
Analytics		AI Human Body Detection, AI Face Detection
Firmware Version		V4.03.R11.C638020W.11201.132200.0000004
Build date		2019-11-15
AUDIO		
Compression		G.711a
Intercom		Support
MANAGEMENT		
Record mode		Manual>Alarm>Motion detection>Timing
Search mode		Inquire by Time/Calendar/Event/Channel
Storage mode		HDD Storage
Backup		Network, USB, SATA
INTERFACE		
Video input		16*BNC (Support Coaxitron)
HDMI output		1*HDMI (MAX:4K)
VGA output		1*VGA (MAX:1080P)
Audio I/O		16/1
Alarm I/O		16/4
Ethernet port		1*10/100/1000Mbps Ethernet port, RJ45 port
PTZ control		1*RS485, Support for multiple PTZ protocol
USB Port		2*USB 2.0 ports
HDD		2*SATA interface (Up to 8TB)
GENERAL		
Temperature		0 °C - + 55 °C
Humidity		10% -90% RH
Power supply		12V/6A
Consumption		<10W (Without HDD)
Weight		Around 4KG
Dimension		440mm(L)* 400.5mm(W)* 60mm(H)

Disclaimer: Design & specifications are subject to change without prior notice.