



ROVER 2CH ALL IN ONE VEHICLE VIDEO RECORDER PORTON













FEATURES-

- Suitable for all personal vehicle, taxi, bus, truck etc.
- Small size, easy installation and dismount, it does not affect the driver's line of sight.
- Insert the card and power on to start recording without additional operating.
- Simultaneously recording interior and exterior condition.
- Having full time, date recording and display on the screen directly.
- Recording driving condition, sound, G-Sensor and GPS data.
- Front view angle approx. 120 degrees. Back view angle approx. 170 degrees.
- Recording track of driving routes which can be shown on Google Map when we play the video.
- Micor SD card Class 10 or above recommend.
- G-sensor sensitivity can be adjusted according to road situations.
 When detect a strong shock, system will start emergency recording and keep the files without being overwritten.
- Professional file formats, without built-in lithium battery, no needs to afraid of heat and bursting concerns, it is the real black box.

DIMENSION-





SPECIFICATIONS

MODEL	RVM07
Chipset	H.264 image compression chip
Sensor Device	Forward facing lens: 720p CMOS Sensor
	Backward facing lens: VGA CMOS Sensor
View Angle	Outside vehicle approx: 120 degree
	Inside vehicle approx: 170 degree
Voltage	Please use 5V±5%, 1A Cigarette lighter adapter
	The machine needs 4.7v to start
Operating Temp	-15°C~+55°C (Inside Vehicle)
Storage Device	Micro SD Card (4G/8G/16G/32G)
	4GB/Class 10 or above specification is available
Recording Frame	Forward facing lens: 1280x720; Highest resolution: 30fps/25fps (NTSC/PAL)
	Backward facing lens: 640x480; Highest resolution: 15fps/15fps (NTSC/PAL)
	Auto record when power up system; backward facing lens can be closed by
	setting of software
Recording Content	Date, time, image, sound, G-sensor data, GPS data
Recording Format	Specific format for software player
Microphone	Build-in high sensitivity of single microphone for automatic voice adjustment
	Auto-calibrating by GPS signals
Time Setup	If GPS is not available, the built-in clock will be used
G-Sensor	Internal 3D G-Sensor
ACCESSORIES	
Standard	(a) 5V cigarette Power adapter (b) USB card reader
	(c) 4 pings, 3.5 inch headphone jack to RCA output cable
	(d) Suction cup bracket (e) Bracket holder (f) Remote control
	(g) Product CD (h) Quick Guide
Optional	(a) Micro SD card (4GB/8GB/16GB/32GB)
	(b) External GPS Mouse (4P Phone Jack Connect)

^{*} Design & specifications subject to change without prior notice