



**ROVER 32CH H.265 5MP-N XVI  
NON-REAL TIME HIGH DEFINITION 6 IN 1  
DVR W/ FACE DETECTION FUNCTION  
2 SATA, 220VAC, NTSC**

# **RXH1732ELME**



## FEATURES

- Support 32ch 5M-N non-real time encoding;
- Support XVI, AHD, TVI, CVI,CVBS, IP video input;
- Supports AI Human Body Detection;
- Supports AI Face Detection;
- Support VGA maximum 1080P output, HDMI up to 4K output;
- BIG 1U Case, 2 SATA(Up to 8TB);
- 1\*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL,4G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function;
- Support WEB, CMS, VMS Platform;
- Support coaxial control;

## INTERFACE



## SPECIFICATIONS

MODEL		RXH1732ELME
<b>VIDEO</b>		
Codec		H.265/H.264
Preview	32ch 5M-N@12fps(6 in 1)/32ch 4M-N@15fps(6 in 1)/32ch 1080P@15fps(6 in 1)/32ch 1080N@15fps(6 in 1)	
Encode	32ch 5M-N@ 6fps(6 in 1)/32ch 4M-N@ 8fps(6 in 1)/32ch 1080P@ 8fps(6 in 1)/32ch 1080N@ 15fps(6 in 1)	
Decode	8ch 5M-N@ 6fps(6 in 1)/16ch 4M-N@ 8fps(6 in 1)/16ch 1080P@ 8fps(6 in 1)/16ch 1080N@ 15fps(6 in 1)	
Multi-mode	Analog:32ch 5M-N/32ch 4M-N/32ch 1080N Digital to analog conversion: support Hybrid:8*1080N(analog)+8*960P(network) IP: 32ch 1080P/16ch 3M/8ch 5M	
Playback		16/8ch
<b>SMART</b>		
Analytics	AI Human Body Detection, AI Face Detection	
Firmware Version	V4.03.R11.C638020W.11201.0423000.0000005	
Build date	2019-09-30	
<b>AUDIO</b>		
Compression		G.711a
Intercom		Support
<b>MANAGEMENT</b>		
Record mode	Manual>Alarm>Motiondetection>Timing	
Search mode	Inquire by Time/Calendar/Event/Channel	
Storage mode	HDD Storage	
Backup	Network, USB, SATA	
<b>INTERFACE</b>		
Video input	32*BNC(Support Coaxitron)	
HDMI output	1*HDMI (MAX:4K)	
VGA output	1*VGA (MAX:1080P)	
Audio I/O	16/1	
Alarm I/O	8/1	
Ethernet port	1*10/100/1000Mbps Ethernet port, RJ45 port	
PTZ control	1*RS485,1*RS232;Support for multiple PTZ protocol	
USB Port	2*USB 2.0 ports	
HDD	2*SATA interface (Up to 8TB)	
<b>GENERAL</b>		
Temperature	0°C - + 55°C	
Humidity	10% -90% RH	
Power supply	12V/4A	
Consumption	<10W (Without HDD)	
Weight	Around 3KG	
Dimension	440mm(L)* 290mm(W)* 50mm(H)	

Disclaimer: Design & specifications are subject to change without prior notice.