



ROVER 16 CHANNEL / 4 PORTS POE NVR
(1 SATA, HDMI & VGA VIDEO OUTPUT,
AUDIO OUTPUT, 48VDC, 2.5A)



RNH1504AKL

FEATURES

- 4*4K video inputs (up to 16*4K) (Access bandwidth 72Mbps);
- HDMI (Max 4K), VGA (Max 1080P) video outputs;
- Mini 1U Case, 1SATA (Up to 8TB);
- H.265A/H.265+/H.265/H.264;
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- PoE power over ethernet, 4 standard PoE ports;
- Automatic networking support, one key in adding equipment;
- Supports ONVIF protocol;
- Cloud services, P2P, push alarm information to phone;
- Supports remote access, ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, Email, 3G, WIFI, IP Search, Alarm Center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Supports more than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Supports WEB, CMS, VMS, Rover 1000 eMobile Platform;

INTERFACE



SPECIFICATIONS

MODEL	RNH1504AKL
SYSTEM	
System	Embedded Linux
VIDEO	
Video Input	4*4K (up to 16*4K) (Access bandwidth 72Mbps)
Playback (Real-time + Non-Real-time)	4K (1*Real-time) /5M (1+1) /4M (2+1) /3M (3+1) /1080P (5+1)
Decode	H.265A/H.265+/H.265/H.264
AUDIO	
Audio Compression	G.711a
MANAGEMENT	
Record Mode	Manual>Alarm>Motion Detection>Timing
Search Mode	Time/Date/Event/Channel/Face
Storage	HDD Storage, Network Storage
Backup	Network, USB, SATA
INTERFACE	
HDMI Output	1*HDMI (Max 4K)
VGA Output	1*VGA (Max 1080P)
Ethernet Port	1*RJ45 1*10/100Mbps Ethernet port
PoE Ports	4 standard PoE ports
Audio I/O	0/1 (3.5mm)
USB Port	2*USB2.0 Ports
HDD	1*SATA Interface (Up to 8TB)
GENERAL	
Temperature	0 °C - + 55 °C
Humidity	10% -90% RH
Power Supply	48V/2.5A
Power Consumption	<10W (Without HDD)
Weight	Around 0.7KG
Dimensions	255mm(L) * 215mm(W) * 44mm(H)

Disclaimer: Design & specifications are subject to change without prior notice.