

ROVER 4K 4/8 & 10/16CH NVR, 1 SATA
UP TO 14TB, 1 VGA, 1 HDMI, AUDIO IN/OUT,
H.265AI/H.265+, NTSC

RNH1504ASKL
RNH1508ASKL
RNH1510ASKL
RNH1516ASKL



FEATURES

- 4*PoE IPC+6*IPC(RNH1504ASKL), 8*PoE IPC+8*IPC(RNH1508ASKL), 10/16Ch *4K video inputs;
- VGA 1080P, HDMI 4K video output;
- Mini 1U Case, 1SATA (Up to 14TB);
- H.265AI/H.265+(compatible H.265/H.264);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- PoE power over ethernet, 4 standard PoE ports(RNH1504ASKL)/ 8 standard POE ports (RNH1508ASKL);
- Automatic network support, a key in adding devices;
- Supports ONVIF protocol;
- Cloud services, P2P, push to phone alarm notification;
- Supports remote access, ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, Email, 3G, WIFI, IP Search, Alarm Center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari, Microsoft Edge);
- Supports for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Supports WEB, CMS, VMS, Rover 1000 eMobile Platform;
- Supports AI functions config like Face Detection, Human Detection and Vehicle Detection etc;

INTERFACE

RNH1504ASKL



RNH1508ASKL



RNH1510ASKL / RNH1516ASKL



SPECIFICATIONS

MODEL	RNH1504ASKL	RNH1508ASKL	RNH1510ASKL	RNH1516ASKL
SYSTEM				
System	Embedded Linux			
VIDEO				
Video Input	4*PoE IPC+6*IPC	8*PoE IPC+8*IPC	10ch4K	16ch4K
Playback (Real-time + Non-Real-time)	4K (1)/5M (1+1)/ 4M(2+1)/3M (2+2)/ 1080P (4+1)	4K (1)/5M (1+1)/ 4M(2)/3M (2+1)/ 1080P (4)	4K (1)/5M (1+1)/ 4M(2+1)/3M (2+2)/ 1080P (4+1)	4K (1)/5M (1+1)/ 4M(2)/3M (2+1)/ 1080P (4)
Decode	H.265AI/H.265+(compatible H.265/H.264)			
AUDIO				
Audio Compression	G.711a			
Intercom	Supported			
MANAGEMENT				
Record Mode	Manual>Alarm>Motion Detection>Timing			
Search Mode	Search by Time/Date/Event/Channel/Face			
Storage	HDD Storage, Network Storage			
Backup	Network, USB, SATA			
Bandwidth	60Mbps	80Mbps shared Incoming/Outgoing	60Mbps	
INTERFACE				
HDMI Output	1*HDMI (Max 4K)			
VGA Output	1*VGA (Max 1080P)			
Ethernet Port	1*RJ45 1*10/100Mbps Ethernet port			
PoE Ports	4 standard PoE ports	8 standard PoE ports	N/A	
Audio I/O	1/1(3.5mm)		0/1(3.5mm)	1/1(3.5mm)
USB Port	2*USB2.0 Ports			
HDD	1*SATA Interface (Up to 14TB)			
GENERAL				
Operating Temperature	0 °C - + 55 °C			
Humidity	10% -90% RH			
Power Supply	48V/2.5A		12V/2A	
Power Consumption	<10W (Without HDD)			
Weight	Around 0.7KG		Around 0.64KG	
Dimensions	255mm(L) * 215mm(W) * 44mm(H)			

Disclaimer: Design & specifications are subject to change without prior notice.