



RWK4G2G24UB

ROVER WIFI NVR KIT ((1) 3MP/8CH WIFI NVR + (4) 3.0MP DUAL LIGHT BULLET CAMERA) LONG DISTANCE

RWK4G2G24UC

ROVER WIFI NVR KIT ((1) 5MP/4CH WIFI NVR + (4) 5.0MP DUAL LIGHT BULLET CAMERA) LONG DISTANCE

RNH1K08KIT

ROVER 3MP/8CH OR 5MP/4CH H.265AI WIFI NVR, 1 SATA UP TO 14TB, HDMI & VGA VIDEO OUTPUT, 12VDC



FEATURES

- Supports DWDR, 3D DNR;
- Day/Night (Auto ICR);
- IR range: 2 infrared lamps, 1 white lamp 20m-30m;
- H.265+(compatible H.265/H.264) high profile, 4Ch(5MP)/8Ch(3MP) WIFI NVR;
- Supports IEEE802.11b/g/n, Dual antenna, 2.4GHz;
- Supports video preview, recording, playback, backup;
- Supports DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari), Supports ARSP;
- Supports WEB, CMS, VMS Platform;

CONNECTION DIAGRAM



Can configure individual camera as a repeater to connect up to eight (8) cascading cameras, upto 800m transmission distance in ideal conditions, check application environment and conduct simulation when necessary.

SPECIFICATIONS

MODEL	RNH1K08KIT
NETWORK VIDEO RECORDER	
SYSTEM	
Operating System	Embedded Linux
VIDEO	
Video Input	8ch 3M/4ch 5M
Playback	8ch 3M/4ch 5M
Video Compression	H.265AI/H.265+(Compatible H.265/H.264)
AUDIO	
Audio Compression	G.711a
Intercom	Supported
MANAGEMENT	
Record Mode	Manual>Alarm>Motion detection>Timing
Search Mode	Search by Time/Calendar/Event/Channel/Face
Storage Mode	HDD Storage, Network Storage
Backup	Network, USB, SATA
WIRELESS PARAMETERS	
Frequency Bands	2.4GHz
IEEE Standard	IEEE802.11b/g/n
INTERFACE	
HDMI Output	1*HDMI (MAX:1080P)
VGA Output	1*VGA (MAX:1080P)
Ethernet Port	1*10/100Mbps Ethernet port, RJ45 port
Audio I/O	1/1(3.5mm)
USB Port	2*USB2.0 ports
HDD	1*SATA interface (Up to 14TB)
GENERAL	
Temperature	0°C- + 55 °C
Humidity	10% -90% RH
Power Supply	12V/2A
Power Consumption	<10W (Without HDD)
Weight	Around 0.64KG
Dimensions	255(L)* 215mm(W)* 44mm(H)

Disclaimer: Design & specifications subject to change without prior notice.

RHBC2D3XG3LR RHBC2D3XG5LR

ROVER 3.0MP 1/2.7" WIFI IP DUAL LIGHT BULLET CAMERA, 2.8MM, (1 LED ARRAY, 1 SPOTLIGHT, 30 METERS IR RANGE) (FOR WIFI NVR KIT ONLY)

ROVER 5.0MP 1/3" WIFI IP DUAL LIGHT BULLET CAMERA, 2.8MM, (1 LED ARRAY, 1 SPOTLIGHT, 30 METERS IR RANGE) (FOR WIFI NVR KIT ONLY)

SPECIFICATIONS

MODEL	RHBC2D3XG3LR	RHBC2D3XG5LR
CAMERA		
Image Sensor	3.0MP 1/2.7" CMOS sensor	5.0MP 1/3" SC401AI CMOS sensor
Minimum Illumination	Color:0.01Lux @(F1.2,AGC ON); 0 Lux with IR B/W: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR	
Shutter Speed	1/50(1/60)s to 1/10,000s	
Lens Size	HD lens 3.6mm@F2.0	
Lens Mount	M12	
Day & Night Mode	IR cut filter with auto switch	
IMAGE		
Maximum Image Resolution	2304*1296	2880*1616
Frame Rate	NTSC: 2304*1296@12fps, 1920*1080@12fps	NTSC: 2880*1616@12fps, 2560*1440@12fps
Video Output Settings	Saturation, Brightness and Contrast are adjustable through IE browser or client software	
COMPRESSION		
Video Compression	H.265+(compatible H.265/H.264) HighProfile, JPEG snapshot	
Bite Rate	0.1Mbps~6Mbps	
Audio Compression	G.711a	
NETWORK PARAMETERS		
Storage	Network storage	
Alarm	Face Detection, Human Detect, Motion Detection, Video Loss, Video Block, etc.	
Network Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP, (HTTPS, SIP, 802.1x, IPv6 option)	
Features	Anti-flicker, Dual-stream, Heartbeat, Password protection	
INTERFACE		
Ethernet	WiFi transfer, Supports direct connection by WPS	
GENERAL		
Temperature	-10°C~+60°C	
Humidity	10%-90% RH	
Power Supply	DC12V±10%	
IR Range	2 infrared lamps, 1 white lamp "IR2":20-30 meters	
Power Consumption	MAX 4W	
Ingress Protection	IP66	
Weight	Around 330g	
Dimensions	66.8mm*170.4mm	

Disclaimer: Design & specifications subject to change without prior notice.