



ROVER 4CH H.265 5MP XVI NON-REAL TIME HIGH DEFINITION 6 IN 1 DVR WITH FACE DETECTION FUNCTION 1 SATA, 220VAC, NTSC

# RXH1704TNMH



## FEATURES

- Support 4ch 5MP non-realtime encoding;
- Supports XVI, AHD, TVI, CVI, CVBS, IP video input;
- Supports AI Human Body Detection;
- Supports AI Face Detection;
- Supports AI Face Search;
- Supports VGA maximum 1080P output, HDMI up to 1080P output;
- Mini 1U Case, 1SATA (Up to 14TB);
- 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Supports ONVIF protocol;
- Cloud services, P2P, alarm information push to phone;
- Supports remote access, support ARSP;
- Supports DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Supports for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Supports WEB, CMS, VMS Platform;
- Supports coaxial control;

## INTERFACE



## SPECIFICATIONS

MODEL		RXH1704TNMH
VIDEO		
Codec		H.265/H.264
Preview		4ch5M-N@20fps (6 in 1) / 4ch4M-N@30fps (6 in 1) / 4ch1080P (6 in 1) default 5M-N
Encode		4ch5M-N@20fps (6 in 1) / 4ch4M-N@30fps (6 in 1) / 4ch1080P (6 in 1) default 5M-N
Decode		4ch5M-N@20fps (6 in 1) / 4ch4M-N@30fps (6 in 1) / 4ch1080P (6 in 1) default 5M-N
Multi-mode		Analog: 4ch 5M-N
		Hybrid: 4*5M-N (analog) + 2*1080P (network)
Playback		IP: 16ch 1080P/8ch 5M 2ch
SMART		
Analytics		AI Human Body Detection, AI Face Detection and AI Face Search
AUDIO		
Compression		G.711a
Intercom		Supported
MANAGEMENT		
Record mode		Manual>Alarm>Motion detection>Timing
Search mode		Inquire by Time/Calendar/Event/Channel
Storage mode		HDD Storage, Network Storage
Backup		Network, USB, SATA
INTERFACE		
Video input		4*BNC (Support Coaxitron)
HDMI output		1*HDMI (MAX:1080P)
VGA output		1*VGA (MAX:1080P)
Audio I/O		1/1
Ethernet port		1*10/100Mbps Ethernet port, RJ45 port
PTZ control		Support for multiple PTZ protocol
USB Port		2*USB 2.0 ports
Storage		1*SATA interface (Up to 14TB)
GENERAL		
Temperature		0 °C - + 55 °C
Humidity		10% -90% RH
Power supply		12V/2A
Consumption		<10W (Without HDD)
Weight		Around 1KG
Dimensions		255mm(L)* 215mm(W)* 44mm(H)

Disclaimer: Design & specifications are subject to change without prior notice.