



ROVER 5MP-N 4CH XVI NON-REAL TIME
HIGH DEFINITION 6 IN 1 DVR, 1 SATA,
220VAC, H.265, NTSC



RXH1704TNMHC

SPECIFICATIONS

MODEL	RXH1704TNMHC	
VIDEO		
Video Compression	H.265/H.264	
Preview	4ch5M-N@20fps (6 in 1)/4ch4M-N@30fps (6 in 1)/ 4ch1080P (6 in 1) default5M-N	
Encode	4ch5M-N@20fps (6 in 1)/4ch4M-N@28fps (6 in 1)/ 4ch1080P@25fps (6 in 1) default5M-N	
Decode	2ch5M-N@20fps (6 in 1)/2ch4M-N@28fps (6 in 1)/ 2ch1080P@25fps (6 in 1) default5M-N	
Multi-mode	Analog: 4ch 5M-N	
	Hybrid: 4*5M-N (analog) +2*1080P (network)	
Playback	IP: 16ch 1080P/8ch 5M 2ch	
SMART		
Analytics	AI Human Body Detection, AI Face Detection and AI Vehicle Detection	
AUDIO		
Coaxial Audio	Supported	
Audio Compression	G.711a	
Intercom	Supported	
MANAGEMENT		
Record Mode	Manual>Alarm>Motion detection>Timing	
Search Mode	Search by Time/Calendar/Event/Channel	
Storage Mode	HDD Storage, Network Storage	
Backup	Network, USB, SATA	
INTERFACE		
Video Input	4*BNC (Support Coaxitron)	
HDMI Output	1*HDMI (MAX: 1080P)	
VGA Output	1*VGA (MAX: 1080P)	
Audio I/O	1/1	
Ethernet Port	1*10/100Mbps Ethernet port, RJ45 port	
PTZ Control	Support for multiple PTZ protocol	
USB Port	2*USB 2.0 ports	
HDD	1*SATA interface (Up to 14TB)	
GENERAL		
Operating Temperature	0 °C - + 55 °C	
Humidity	10% -90% RH	
Power supply	12V/2A	
Power Consumption	<10W (Without HDD)	
Weight	Around 1 KG	
Dimensions	255mm(L)* 215mm(W)* 44mm(H)	

Disclaimer: Design & specifications are subject to change without prior notice.

FEATURES

- Supports 4ch 5M-N Non-real time encoding;
- Supports XVI, AHD, TVI, CVI, CVBS, IP video input;
- Supports AI Human Body Detection;
- Supports AI Face Detection;
- Supports AI Vehicle Detection;
- Supports VGA maximum 1080P output, HDMI up to 1080P output;
- Mini 1U Case, 1SATA (Up to 14TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- A key to add equipment;
- Supports ONVIF protocol;
- Cloud services, P2P, alarm information push to phone;
- Supports remote access, ARSP;
- Supports DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Circuit protection; unique triple watchdog function;
- Supports WEB, CMS, VMS Platform;
- Supports coaxial control;
- Supports coaxial audio;

INTERFACE

