

ROVER H.265+ 5MP-N XVI NON-REAL  
TIME HIGH DEFINITION 6 IN 1 DVR  
W/ FACE DETECTION FUNCTION,  
1 SATA , 220VAC, NTSC

**RXH1708TLME/  
RXH1716TLME**



## FEATURES

- Support 8ch and 16ch 5M-N Non-real-time encoding;
- Supports AI Human Body Detection;
- Supports AI Face Detection;
- Support XVI,AHD, TVI,CVI, CVBS, IP video input;
- Mini 1U Case, 1 SATA(Up to 8TB);
- 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 4G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function;
- Support WEB, CMS, VMS Platform;
- Support coaxial control;

## INTERFACE

RXH1708TLME



RXH1716TLME



## SPECIFICATIONS

MODEL	RXH1708TLME	RXH1716TLME
<b>VIDEO</b>		
Codec	H.265+	
Preview	8 5M-N@12fps (6 in 1)	16 5M-N@12fps (6 in 1)
Encode	8 5M-N@6fps (6 in 1)	16 5M-N@6fps (6 in 1)
Decode	4 5M-N@6fps (6 in 1)	8 5M-N@6fps (6 in 1)
Multi-mode	Analog:8ch 5M-N/8ch 4M-N Digital to analog conversion support (except 8ch 5M-N mode) Hybrid:8ch 4M-N(analog)+ 8ch 1080P(network) IP:16ch 1080P/8ch 5M	Analog:16ch 5M-N/16ch 4M-N Digital to analog conversion support (except 16ch 5M-N mode) Hybrid:8ch 1080N(analog)+ 8ch 960P(network) IP:8ch 1080P + 8ch 960P/ 4ch 3M/4ch 5M
Playback	4ch	16ch / 8ch
<b>SMART</b>		
Analytics	AI Human Body Detection, AI Face Detection	
Firmware Version	V4.03.R11.6758020V. 11201.042300.0000005	V4.03.R11.6758020Q. 11201.142300.0000005
Build date	2020-01-06	
<b>AUDIO</b>		
Compression	G.711a	
<b>MANAGEMENT</b>		
Record mode	Manual>Alarm>Motion detection>Timing	
Search mode	Inquire by Time/Calendar/Event/Channel	
Storage mode	HDD Storage	
Backup	USB, SATA	
<b>INTERFACE</b>		
Video input	8*BNC (Support Coaxitron)	16*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:1080P)	1*HDMI (MAX:4K)
VGA output	1*VGA (MAX:1080P)	
Audio I/O	1/1	2/1
Alarm I/O	0/0	
Ethernet port	1*10/100 Ethernet port, RJ45 port	
PTZ control	1*RS485, Support for multiple PTZ protocol	
USB Port	2*USB 2.0 ports	
HDD	1*SATA interface (Up to 8TB)	
<b>GENERAL</b>		
Temperature	0 °C - + 55 °C	
Humidity	10% -90% RH	
Power supply	12V/2A	
Consumption	<10W (Without HDD)	
Weight	Around 1KG	
Dimension	255mm(L)* 236mm(W)* 44mm(H)	

Disclaimer: Design & specifications are subject to change without prior notice.