



ROVER 5MP-N 8/16CH H.265 XVI  
NON-REAL TIME HIGH DEFINITION  
6 IN 1 DVR 1 SATA, 220VAC, NTSC

**RXH1708TNLME**  
**RXH1716TNLME**



## SPECIFICATIONS

## FEATURES

- Supports 8/16ch 5M non-real time encoding;
- Supports AI Human Body Detection;
- Supports AI Face Detection;
- Supports AI Face Search;
- Supports XVI, AHD, TVI, CVI, CVBS, IP video input;
- Supports VGA maximum 1080P output, HDMI up to 2K/4K output;
- Mini 1U Case, 1 SATA (Up to 14TB);
- 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Supports ONVIF protocol;
- Cloud services, P2P, alarm information push to phone;
- Supports remote access, support ARSP;
- Supports DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Perfect protection circuit, unique triple watchdog function;
- Supports WEB, CMS, VMS Platform;
- Supports coaxial control;

## INTERFACE

RXH1708TNLME



RXH1716TNLME



MODEL	RXH1708TNLME	RXH1716TNLME
<b>VIDEO</b>		
Codec	H.265+/H.265/H.264	
Preview	8ch5M-N@12fps(6 in 1)/ 8ch4M-N@15fps(6 in 1)/ 8*1080P@15fps(XVI),default 5M-N	16ch5M-N@12fps(6 in 1)/ 16ch 4M-N@15fps(6 in 1), default 5M-N
Encode	8*5M-N@12fps(6 in 1)/ 8*4M-N@15fps (6 in 1)/ 8*1080P@15fps (XVI), default:5M-N	16ch5M-N@6fps(6 in 1)/ 16ch 4M-N@8fps(6 in 1), default 5M-N
Decode	2*5M-N@12fps(6 in 1)/ 2*4M-N@15fps (6 in 1)/ 2*1080P@15fps (XVI), default:5M-N	8ch5M-N@6fps(6 in 1)/ 8ch 4M-N@8fps(6 in 1), default 5M-N
Multi-mode	Analog: 8ch 5M-N hybrid:8*5M-N (analog) +4*1080P (network) IP:16ch 1080P/8ch 5M	Analog: 16ch 5M-N hybrid:16*5M-N (analog) +4*1080P (network) IP: 16ch 1080P/4ch 5M
Playback	4ch	16ch
<b>SMART</b>		
Analytics	AI Human Body Detection, AI Face Detection and AI Face Search	
<b>AUDIO</b>		
Compression	G.711a	
Intercom	Supported	
<b>MANAGEMENT</b>		
Record mode	Manual>Alarm>Motion detection>Timing	
Search mode	Inquire by Time/Calendar/Event/Channel	
Storage mode	HDD Storage, Network Storage	
Backup	Network, USB, SATA	
<b>INTERFACE</b>		
Video input	8*BNC(Support Coaxitron)	16*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:1080P)	
VGA output	1*VGA (MAX:2K)	1*VGA (MAX:4K)
Audio I/O	1/1	
Ethernet port	1*10/100Mbps Ethernet port, RJ45 port	
PTZ control	1*RS485, Support for multiple PTZ protocol	
USB Port	2*USB 2.0 ports	
HDD	1*SATA interface (Up to 14TB)	
<b>GENERAL</b>		
Operating Temperature	0 °C - + 55 °C	
Humidity	10% -90% RH	
Power supply	12V/2A	
Power Consumption	<10W (Without HDD)	
Weight	Around 1KG	
Dimensions (L*W*H)	255mm*215mm*44mm	255mm*236mm*44mm

Disclaimer: Design & specifications are subject to change without prior notice.