



**ROVER 5MP-N 16CH H.265+ XVI  
NON-REAL TIME HIGH DEFINITION 6 IN 1  
DVR 2 SATA, 220VAC, NTSC**

**RXH1716BNLME**



## FEATURES

- Supports 16ch 5M-non-real-time encoding;
- Supports XVI, AHD, TVI, CVI, CVBS, IP video input;
- Supports VGA maximum 1080P output, HDMI up to 1080P output;
- 1.5U Case, 2 SATA (Up to 14TB);
- 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Supports ONVIF protocol;
- Cloud services, P2P, alarm information push to phone;
- Supports remote access, support ARSP;
- Supports DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Perfect protection circuit, unique triple watchdog function;
- Supports WEB, CMS, VMS Platform;
- Supports coaxial control;
- Supports human detection, face detection and other intelligence;

## INTERFACE



## SPECIFICATIONS

| MODEL             |  | RXH1716BNLME  |
|-------------------|--|---|
| <b>VIDEO</b>      |  |   |
| Codec             |  | H.265+/H.265/H.264  |
| Preview           |  | 16ch5M-N@12fps(6 in 1)/16ch 4M-N@15fps(6 in 1), default 5M-N                          |
| Encode            |  | 16ch5M-N@6fps(6 in 1)/16ch 4M-N@8fps(6 in 1), default 5M-N                            |
| Decode            |  | 8ch5M-N@6fps(6 in 1)/8ch 4M-N@8fps(6 in 1), default 5M-N                              |
| Multi-mode        |  | Analog: 16ch 5M-N<br>hybrid:16*5M-N(analog)+4*1080P(network)<br>IP: 16ch 1080P/4ch 5M |
| Playback          |  | 16ch  |
| <b>AUDIO</b>      |  |   |
| Compression       |  | G.711a  |
| Intercom          |  | Supported   |
| <b>MANAGEMENT</b> |  |   |
| Record mode       |  | Manual>Alarm>Motion detection>Timing  |
| Search mode       |  | Inquire by Time/Calendar/Event/Channel  |
| Storage mode      |  | HDD Storage, Network Storage  |
| Backup            |  | Network, USB, SATA  |
| <b>INTERFACE</b>  |  |   |
| Video input       |  | 16*BNC (Support Coaxitron)  |
| HDMI output       |  | 1*HDMI (MAX:4K)   |
| VGA output        |  | 1*VGA (MAX:1080P)   |
| Audio I/O         |  | 6/1   |
| Alarm I/O         |  | 4/1   |
| Ethernet port     |  | 1*10/100Mbps Ethernet port, RJ45 port   |
| PTZ control       |  | 1*RS485, Support for multiple PTZ protocol  |
| USB Port          |  | 2*USB2.0 ports  |
| HDD               |  | 2*SATA interface (Up to 14TB)   |
| <b>GENERAL</b>    |  |   |
| Temperature       |  | 0 °C - + 55 °C  |
| Humidity          |  | 10% -90% RH   |
| Power Supply      |  | 12V/4A  |
| Power Consumption |  | <10W (Without HDD)  |
| Weight            |  | Around 1.8KG  |
| Dimension         |  | 310mm(L)* 298mm(W)* 60mm(H)   |

Disclaimer: Design & specifications are subject to change without prior notice.