



ROVER 5MP-N 32CH XVI NON-REAL TIME HIGH DEFINITION 6 IN 1 DVR  
2/4 SATA, 220VAC, H.265+, NTSC

**RXH1732ENLME**  
**RXH1732FNLME**



## FEATURES

- Supports 32ch 5M-N non-realtime encoding;
- Supports AHD, TVI, CVI, CVBS, IP video input;
- HDMI/VGA video output;
- BIG 1U Case, 2 SATA(Up to 14TB)(RXH1732ENLME)/  
2U Case, 4 SATA(Up to 14TB)(RXH1732FNLME);
- 1\*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking supported, a key to add equipment;
- Supports the ONVIF protocol;
- Cloud services, P2P, alarm push notification to phone;
- Supports remote access, supports ARSP;
- Supports DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Supports for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Supports WEB, CMS, VMS, Rcloud Platform;
- Supports coaxial control;
- Supports intelligent video analytics i.e. Human shape detection, Face detection, Car shape detection;

## INTERFACE

RXH1732ENLME



RXH1732FNLME



## SPECIFICATIONS

MODEL	RXH1732ENLME	RXH1732FNLME
<b>VIDEO</b>		
Codec	H.265+/H.265/H.264	
Preview	32ch 5M-N@12fps(6 in 1)/32ch 4M-N@15fps(6 in 1)/ 32ch 1080P@15fps(XVI), default 5M-N	
Encode	32ch 5M-N@6fps(6 in 1)/32ch 4M-N@8fps(6 in 1)/ 32ch 1080P@8fps(XVI), default 5M-N	
Decode	8ch 5M-N@6fps(6 in 1)/16ch 4M-N@8fps(6 in 1)/16ch 1080P@8fps(XVI), default 5M-N	
Multi-mode	Analog:32ch 5M-N/32ch 4M-N/32ch 1080N Hybrid:16ch5M-N(analog)+ 16ch5M(network)	
Playback	IP: 32ch 4K/16ch 5M 8ch	
<b>AUDIO</b>		
Compression	G.711a	
Intercom	Supported	
<b>MANAGEMENT</b>		
Record Mode	Manual>Alarm>Motion detection>Timing	
Search Mode	Search by Time/Calendar/Event/Channel	
Storage Mode	HDD Storage, Network Storage	
Backup	Network, USB, SATA	
<b>INTERFACE</b>		
Video Input	32*BNC (Support Coaxitron)	
HDMI Output	1*HDMI (MAX:4K)	
VGA Output	1*VGA (MAX:1080P)	
Audio I/O	16/1	
Alarm I/O	8/1	16/4
Ethernet Port	1*10/100/1000Mbps Ethernet port, RJ45 port	
PTZ Control	1*RS485, 1 RS232; Supports multiple PTZ protocol	
USB Port	2*USB2.0 ports	
HDD	2*SATA interface (Up to 14TB)	4*SATA interface (Up to 14TB)
<b>GENERAL</b>		
Operating Temperature	0°C - + 55°C	
Humidity	10% -90% RH	
Power Supply	12V/4A	12V/6A
Power Consumption	<10W(Without HDD)	
Weight	Around 3KG	Around 4KG
Dimensions (L*W*H)	440mm*290mm*50mm	440mm*400.5mm*60mm

Disclaimer: Design & specifications are subject to change without prior notice.