

RXH1732ENLME



RXH1732ELMEC



RXH1732FNLME/RXH1732FLMEC



ROVER 5MP-N 32CH XVI NON-REAL  
TIME HIGH DEFINITION 6 IN 1 DVR  
2/4 SATA, 220VAC, H.265+, NTSC

**RXH1732ENLME**  
**RXH1732ELMEC**  
**RXH1732FNLME**  
**RXH1732FLMEC**



## FEATURES

- Supports 32Ch 5M-N non-realtime encoding;
- Supports AHD, TVI, CVI, CVBS, IP video input;
- HDMI/VGA video output;
- BIG 1U Case, 2 SATA(Up to 14TB)(RXH1732ENLME/RXH1732ELMEC)/  
2U Case, 4 SATA(Up to 14TB)(RXH1732FNLME/RXH1732FLMEC);
- 1\*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking supported, a key to add equipment;
- Supports ONVIF protocol;
- Cloud services, P2P, alarm push notification to phone;
- Supports remote access, supports ARSP;
- Supports DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI,  
IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Supports for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Supports WEB, CMS, VMS, Rcloud Platform;
- Supports coaxial control;
- Supports coaxial audio (RXH1732ELMEC/RXH1732FLMEC);
- Supports intelligent video analytics i.e. Human detection,  
Face detection, Vehicle detection;

## INTERFACE

RXH1732ENLME/RXH1732ELMEC



RXH1732FNLME/RXH1732FLMEC



## SPECIFICATIONS

MODEL	RXH1732ENLME	RXH1732ELMEC	RXH1732FNLME	RXH1732FLMEC
<b>VIDEO</b>				
Codec	H.265+/H.265/H.264			
Preview	32Ch 5M-N@12fps(6 in 1)/32Ch 4M-N@15fps(6 in 1)/ 32Ch 1080P@15fps(XVI), default 5M-N			
Encode	32Ch 5M-N@6fps(6 in 1)/32Ch 4M-N@8fps(6 in 1)/ 32Ch 1080P@8fps(XVI), default 5M-N			
Decode	8Ch 5M-N@6fps(6 in 1)/16ch 4M-N@8fps(6 in 1)/16Ch 1080P@8fps(XVI), default 5M-N			
Multi-mode	Analog: 32Ch 5M-N/32Ch 4M-N/32Ch 1080N			
	Hybrid: 16Ch5M-N(analog)+ 16Ch5M(network)			
Playback	IP: 32Ch 4K/16Ch 5M 8Ch			
<b>AUDIO</b>				
Compression	G.711a			
Coaxial audio	N/A	Supported	N/A	Supported
Intercom	Supported			
<b>MANAGEMENT</b>				
Record Mode	Manual>Alarm>Motion detection>Timing			
Search Mode	Search by Time/Calendar/Event/Channel			
Storage Mode	HDD Storage, Network Storage			
Backup	Network, USB, SATA			
<b>INTERFACE</b>				
Video Input	32*BNC (Support Coaxitron)			
HDMI Output	1*HDMI (MAX:4K)			
VGA Output	1*VGA (MAX:1080P)			
Audio I/O	16/1			
Alarm I/O	8/1		16/4	
Ethernet Port	1*10/100/1000Mbps Ethernet port, RJ45 port			
PTZ Control	1*RS485, 1 RS232; Supports multiple PTZ protocol			
USB Port	2*USB2.0 ports			
HDD	2*SATA interface (Up to 14TB)		4*SATA interface (Up to 14TB)	
<b>GENERAL</b>				
Operating Temperature	0°C - + 55°C			
Humidity	10% -90% RH			
Power Supply	12V/4A		12V/6A	
Power Consumption	<10W(Without HDD)			
Weight	Around 3KG		Around 4KG	
Dimensions (L*W*H)	440mm*290mm*50mm		440mm*400.5mm*60mm	

Disclaimer: Design & specifications are subject to change without prior notice.