



ROVER 4CH H.265 5.0MP XVI NON-REAL TIME HIGH DEFINITION 6 IN 1 DVR, 1 SATA, 220VAC, NTSC

**RXH1804TGS2**  
**RXH1804TNGS**



## FEATURES

- Support 4ch 5M non-real time encoding;
- Support XVI,AHD, TVI,CVI, CVBS, IP video input;
- Support VGA maximum 1080P output, HDMI up to 4K output;
- Mini 1U Case, 1SATA(Up to 8TB);
- 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 4G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function;
- Support WEB, CMS, VMS Platform;
- Support coaxial control;

## SPECIFICATIONS

| MODEL             | RXH1804TGS2   | RXH1804TNGS |
|-------------------|---|-------------|
| <b>VIDEO</b>      |   |             |
| Codec             | H.265+  |             |
| Preview           | 4*5M@12fps (6 in 1);4*4M@15fps (6 in 1);<br>4*3M@18fps (6 in 1);4*1080P (6 in 1)            |             |
| Encode            | 4*5M@6fps (6 in 1);4*4M@8fps (6 in 1);<br>4*3M@10fps (6 in 1);4*1080P@18fps(6 in 1)         |             |
| Decode            | 4*5M@6fps (6 in 1);4*4M@8fps (6 in 1);<br>4*3M@10fps (6 in 1);4*1080P@18fps(6 in 1)         |             |
| Multi-mode        | Analog:4*5M; 4*4M;<br>Hybird:2*4M(analog)+2*4M(network)<br>IP:16*1080P;9*1080P;16*960P;4*5M |             |
| Playback          | 4ch   |             |
| <b>AUDIO</b>      |   |             |
| Compression       | G.711a  |             |
| Intercom          | Support   |             |
| <b>MANAGEMENT</b> |   |             |
| Record mode       | Manual>Alarm>Motiondetection>Timing   |             |
| Search mode       | Inquire by Time/Calendar/Event/Channel  |             |
| Storagemode       | HDD Storage   |             |
| Backup            | Network, USB, SATA  |             |
| <b>INTERFACE</b>  |   |             |
| Video input       | 4*BNC (Support Coaxitron)   |             |
| HDMI output       | 1*HDMI (MAX:4K)   |             |
| VGA output        | 1*VGA (MAX:1080P)   |             |
| Audio I/O         | 1/1   |             |
| Ethernet port     | 1*10/100Mbps Ethernet port, RJ45 port   |             |
| PTZ control       | Coaxial Control, Support multiple PTZ protocol  |             |
| USB Port          | 2*USB2.0 ports  |             |
| HDD               | 1*SATA interface (Up to 8TB)  |             |
| <b>GENERAL</b>    |   |             |
| Temperature       | 0 °C - + 55 °C  |             |
| Humidity          | 10% -90% RH   |             |
| Power supply      | 12V/2A  |             |
| Consumption       | <10W(Without HDD)   |             |
| Weight            | Around1KG   |             |
| Dimension         | 255mm(L)* 236mm(W)* 44mm(H)   |             |

Disclaimer: Design & specifications are subject to change without prior notice.