



ROVER 4K-N 4/8CH XVI NON-REAL TIME HIGH DEFINITION 6 IN 1 DVR, W/ FACE DETECTION FUNCTION, 1 SATA , 220VAC, H.265+, NTSC, IOT MODULE (RXH1808TNGSC ONLY)

**RXH1804TNGSC**  
**RXH1808TNGSC**



## FEATURES

- Supports 4/8ch 4K-N Non-real time encoding;
- Supports AI Human Body Detection;
- Supports AI Face Detection;
- Supports AI Vehicle Detection;
- Supports IoT Module (RXH1808TNGSC only);
- Supports XVI, AHD, TVI, CVI, CVBS, IP video input;
- Supports VGA maximum 1080P output, HDMI up to 4K output;
- Mini 1U Case, 1SATA (Up to 14TB);
- 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- A key to add equipment;
- Supports ONVIF protocol;
- Cloud services, P2P, alarm information push to phone;
- Supports remote access; ARSP;
- Supports DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Circuit protection; unique triple watchdog function;
- Supports WEB, CMS, VMS Platform;
- Supports coaxial control;
- Supports coaxial audio;

RXH1804TNGSC



RXH1808TNGSC



## SPECIFICATIONS

MODEL	RXH1804TNGSC	RXH1808TNGSC
<b>VIDEO</b>		
Video Compression	H.265+/H.265/H.264	
Preview	4ch4K-N@12fps(6 in 1)/ 4ch4M@15fps(6 in 1)/ 4ch3M@18fps(6 in 1)/ 4ch1080P(6 in 1)default:4K-N	8ch4K-N@12fps(6 in 1)/ 8ch4M@15fps(6 in 1)/ 8ch3M@18fps(6 in 1)/ 8ch1080P(6 in 1)default:4K-N
Encode	4ch4K-N@12fps(6 in 1)/ 4ch4M@15fps(6 in 1)/ 4ch3M@18fps(6 in 1)/ 4ch1080P(6 in 1)default:4K-N	8ch4K-N@8fps(6 in 1)/ 8ch4M@10fps(6 in 1)/ 8ch3M@12fps(6 in 1)/ 8ch1080P@18fps(6 in 1)default:4K-N
Decode	1ch4K-N@12fps(6 in 1)/ 1ch4M@15fps(6 in 1)/ 1ch3M@18fps(6 in 1)/ 1ch1080P default:4K-N	8ch4K-N@8fps(6 in 1)/ 8ch4M@10fps(6 in 1)/ 8ch3M@12fps(6 in 1)/ 8ch1080P@18fps(6 in 1)default:4K-N
Multi-mode	Analog: 4ch 4K-N Hybrid: 4*4K-N (analog) +4*5M (network) IP:16ch 1080P/16ch 5M	Analog: 8ch 4K-N Hybrid: 8ch4K-N (analog) +4ch5M (network) IP:16ch 1080P/8ch 5M
Playback	4/2/1ch	8ch
<b>AUDIO</b>		
Coaxial Audio	Supported	
Audio Compression	G.711a	
Intercom	Supported	
<b>MANAGEMENT</b>		
Record Mode	Manual>Alarm>Motion Detection>Timing	
Search Mode	Search by Time/Calendar/Event/Channel	
Storage Mode	HDD Storage, Network Storage	
Backup	Network, USB, SATA	
<b>INTERFACE</b>		
Video Input	4*BNC (Supports Coaxitron)	8*BNC (Supports Coaxitron)
HDMI Output	1*HDMI (MAX:4K)	
VGA Output	1*VGA (MAX:1080P)	
Audio I/O	1/1	
Ethernet Port	1*10/100Mbps Ethernet port, RJ45 port	
PTZ Control	Support for multiple PTZ protocols	
USB Port	2*USB2.0 ports	
HDD	1*SATA interface (Up to 14TB)	
<b>GENERAL</b>		
Temperature	0°C - + 55°C	
Humidity	10% -90% RH	
Power Supply	12V/2A	
Consumption	<10W(Without HDD)	
Weight	Around 1 kg	
Dimensions	255mm(L)* 215mm(W)* 44mm(H)	

Disclaimer: Design & specifications are subject to change without prior notice.