

ROVER 5MP 8/16CH XVI NON-REAL
TIME HIGH DEFINITION 6 IN 1 DVR,
2 SATA, 220VAC, H.265+, NTSC

RXH1808DAGS
RXH1816DANGS



FEATURES

- Supports 8/16 ch 5M non-real time encoding;
- Supports XVI, AHD, TVI, CVI, CVBS, IP video input;
- Supports VGA maximum 1080P output, HDMI up to 4K output;
- 1U Case, 2 SATA(Up to 14TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking supported, a key to add equipment;
- Supports the Onvif protocol;
- Cloud services, P2P, alarm push notification to phone;
- Supports remote access, support ARSP;
- Supports DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 4G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Supports for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Supports WEB, CMS, VMS, Rcloud Platform;
- Supports coaxial control;
- Supports intelligent analytic i.e.: Human shape detection, Face detection, Car shape detection (RXH1816DANGS);

INTERFACE

RXH1808DAGS



RXH1816DANGS



SPECIFICATIONS

MODEL	RXH1808DAGS	RXH1816DANGS
VIDEO		
Codec	H.265+	H.265+/H.265/H.264
Preview	8*5M@12fps(6 in 1); 8*4M@15fps(6 in 1); 8*3M@18fps(6 in 1);8*1080P(6 in 1)	16ch4K@7.5fps(6 in 1)/16ch5M@12.5fps(6 in 1)/ 16ch4M@15fps(6 in 1)/16ch3M@18fps(6 in 1)/ 16ch1080P(6 in 1)
Encode	8*5M@6fps(6 in 1); 8*4M@8fps(6 in 1); 8*3M@10fps(6 in 1); 8*1080P@18fps(6 in 1)	16ch4K@4fps(6 in 1)/16ch5M@6fps(6 in 1)/ 16ch4M@9fps(6 in 1)/16ch3M@10fps(6 in 1)/ 16ch1080P@16fps(6 in 1)
Decode	8*5M@6fps(6 in 1); 8*4M@8fps(6 in 1); 8*3M@10fps(6 in 1); 8*1080P@18fps(6 in 1)	4ch4K@4fps(6 in 1)/4ch5M@6fps(6 in 1)/ 4ch4M@9fps(6 in 1)/4ch3M@10fps(6 in 1)/ 4ch1080P@16fps(6 in 1)
Multi-mode	Analog:8*5M; 8*4M;8*1080P Hybird:4*4M@15fps(analog) +4*4M@18fps(network) IP: 8*1080P+8*960P;4*3M;4*5M	Analog:16ch4K;16ch5M; Hybrid:16ch4K (analog) +16ch4K (network) IP: 16ch4K;16ch5M;
Playback	8ch	4K:4ch;5M: 6ch
AUDIO		
Compression	G.711a	
Intercom	Supported	
MANAGEMENT		
Record Mode	Manual>Alarm>Motiondetection>Timing	
Search Mode	Inquire by Time/Calendar/Event/Channel	
Storage Mode	HDD Storage	HDD Storage, Network Storage
Backup	Network, USB, SATA	
INTERFACE		
Video Input	16*BNC (Support Coaxitron)	
HDMI Output	1*HDMI (MAX:4K)	
VGA Output	1*VGA (MAX:1080P)	
Audio I/O	1/1	6/1
Alarm I/O	N/A	4/1
Ethernet Port	1*10/100Mbps Ethernet port, RJ45 port	
PTZ Control	1*RS485, Support for multiple PTZ protocol	
USB Port	3*USB2.0 ports	
HDD	2*SATA interface (Up to 8TB)	
GENERAL		
Operating Temperature	0°C - + 55°C	
Humidity	10% -90% RH	
Power Supply	12V/4A	
Power Consumption	<10W(Without HDD)	
Weight	Around 1.8KG	
Dimension	350mm(L)* 296mm(W)* 44mm(H)	